

DIRECT VENT FLARE-FF-45-H

FLARE FRAMELESS MODERN FRONT FACING FIREPLACE

SKU: DVFF45H

Item	Details			
Gas Type Options	Natural Gas (NG) or Liquid Propane (LP)			
Safety Standards	CSA File # 263124 - ANSI Z21.88 - CSA 2.33			
Gas Valve System	SIT Proflame II			
Electrical	110 Volts, 15 Amps (Dedicated Circuit Recommended)			
Glass Height	24"			
Safety Barrier	Safety Screen (Standard Barrier) - SS		Triple Glass (Optional Upgrade) - CG	
Weights	In Crate		No Crate	
	328 lbs. (SS)	359 lbs. (DG)	320 lbs. (SS)	333 lbs. (DG)
Included Features	Power Supply, Wall Switch, Remote, Option of Classic Media			
Cool Wall Tech	Allows television or art piece 12" above fireplace opening			
Burner	Standard: Advanced 3D Multi-Row Burner Upgrade: Elevated Summit Burner			
Optional Features	Triple Glass	Reflective Back	Summer Kits	Features Page
	RGB LEDs	Reflective Sides	Power Vents	
Interior Media	Flare Fireplace Media Options			

PRODUCT SPECIFICATIONS

- The Flare Fireplace is certified for use with either Natural Gas (NG) or Propane (LP)
- The Flare Fireplace operates with a direct vent, balanced flue system. A direct vent gas fireplace is room-sealed using ceramic glass.
- The Flare Fireplace use’s double pipe vent flue to pull in fresh air from outside & release exhaust gases to the outside. Clearances to combustible materials MUST be maintained. Refer to [Installation Manual](#) for clearance distances.
- The Flare Fireplace must be properly connected to a venting system.
- The Flare Fireplace must be installed according to requirements as presented in the [Installation Manual](#), as well as complying with all local codes. If no codes exist, then the current CSA installation code must be followed.

PARTS INCLUDED:

- Flare Fireplace
- Ceramic Glass Panel(s)
- Invisible Mesh Safety Screen
- Option of “Classic” Media
- Complete Electronic Ignition Pilot
- Spare Parts Kit
- Telescopic Legs & Mounting Brackets
- AC Power Supply, Remote, & Wall Switch

OPTIONAL FEATURES:

- Triple Glass Safety Barrier
- Reflective Black Ceramic Glass Back & Sides
- Summer Kit Heat Control System
- Home Automation (3rd Party Support Only)
- Battery Backup (Screen Units Only)
- Summit Log Burner

APPROVED VENTING:

- [DuraVent](#)
- [ICC](#)
- Natural Draft Pipe Size: 4x6
- Power Vented Pipe Size: 3x5

GAS PRESSURE & POWER OUTPUT

NG EFFICIENCY 82% | LP EFFICIENCY 83%

SIT										
GAS TYPE	INLET PRESSURE		MANIFOLD PRESSURE	MAX BTU INPUT	ORIFICE SIZE			BURNER SIZE		
	MIN	MAX			LEFT BURNER	CENTER BURNER	RIGHT BURNER	LEFT BURNER	CENTER BURNER	RIGHT BURNER
NG	7.0" WC	8.0" WC	3.5" WC	36,000	0	1100	0	0	32"	0
LP	10.0" WC	11.0" WC	9.5" WC	28,000	0	320	0			
HONEYWELL (LEGACY)										
GAS TYPE	INLET PRESSURE		MANIFOLD PRESSURE	MAX BTU INPUT	ORIFICE SIZE			BURNER SIZE		
	MIN	MAX			LEFT BURNER	CENTER BURNER	RIGHT BURNER	LEFT BURNER	CENTER BURNER	RIGHT BURNER
NG	7.0" WC	8.0" WC	4.3" WC	36,800	0	1000	0	0	32"	0
LP	10.0" WC	11.0" WC	7.8" WC	26,300	0	320	0			
GV60 (LEGACY)										
GAS TYPE	INLET PRESSURE		MANIFOLD PRESSURE	MAX BTU INPUT	ORIFICE SIZE			BURNER SIZE		
	MIN	MAX			LEFT BURNER	CENTER BURNER	RIGHT BURNER	LEFT BURNER	CENTER BURNER	RIGHT BURNER
NG	7.0" WC	8.0" WC	4.7" WC	36,800	0	1000	0	0	32"	0
LP	10.0" WC	11.0" WC	10.4" WC	26,300	0	320	0			

For more information on Flare, or our amazing features, please visit: <https://www.flarefireplaces.com>