

DIRECT VENT FLARE-TRA-BON-42

FRAMELESS TRADITIONAL 42" BONFIRE FIREPLACE
Product SKU: **TRABON42**

Item	Details			
Gas Type Options	Standard: Natural Gas (NG)		Liquid Propane (LP)	
Safety Standards	CSA File # 263124 - ANSI Z21.88 - CSA 2.33			
Gas Valve System	SIT Proflame II			
Electrical	110 Volts, 15 Amps (Dedicated Circuit Recommended)			
Viewing Window	38 11/16" x 32"			
Safety Barrier	Standard: Safety Screen (SS)		Upgrade: Double Glass - Passive (DG)	
Weights	<u>In Crate</u>		<u>No Crate</u>	
	460 lbs. (SS)	510 lbs. (DG)	440 lbs. (SS)	490 lbs. (DG)
Included Features	Power Supply, Wall Switch, Remote, RGB LEDs, & One Classic Media			
Heat Management	Standard: Free Flow	Optional: Passive Heat Flex	Optional: Active Heat Flex	
Cool Wall Tech	Mount a TV 12" above glass window.			
Burner	Bonfire Burner			
Optional Features	Double Glass Passive	Reflective Back	Summer Kits	Brick Interiors
		Reflective Sides	Power Vents	Features Page
Interior Media	Flare Fireplace Media Options			

PRODUCT SPECIFICATIONS

- The Flare Fireplace is certified for use with either Natural Gas (NG) or Propane (LP)
- The Flare Fireplace operates with a direct vent, balanced flue system. A direct vent gas fireplace is room-sealed using ceramic glass. The fireplace must be properly connected to a venting system.
- The Flare Fireplace uses double pipe vent flue to pull in fresh air from outside & release exhaust gases to the outside.
- Clearances to combustible materials MUST be maintained. Contact support@flarefireplaces.com with any questions or details.
- The Flare Fireplace must be installed according to the requirements presented, as well as complying with all local codes. If no codes exist, then the current CSA installation code must be followed.



PRODUCT SHEET: FLARE-TR-BON-42

PARTS INCLUDED:

- Traditional 42" Fireplace
- Inner Ceramic Glass Panel
- Invisible Mesh Safety Screen
- RGB LEDs
- Option of "Classic" Media
- Complete Electronic Ignition System
- Spare Parts Kit
- Telescopic Legs & Mounting Brackets
- AC Power Supply, Remote, & Wall Switch
- Bonfire Burner

OPTIONAL FEATURES:

- Double Glass Safety Barrier
- Brick Interior
- Reflective Black Glass Interior
- Large Oak Log Set
- Summer Kit
- Passive Heat Flex
- Active Heat Flex
- Home Automation (3rd Party Support Only)
- Battery Backup
- Optional Power Venting

APPROVED VENTING:

- [DuraVent](#)
- [ICC](#)
- Natural Draft Pipe Size: 5x8
- Power Vented Pipe Size: 3x5

SIT - Bonfire						
Fuel	Inlet Pressure		Hole Size	Max BTU	Orifice Size	
	Min.	Max.			Orifice 1	Orifice 2
NG	7" WC	8" WC	3mm	37,000	900	380
LP	10" WC	11" WC	3mm	28,000	260	80

NG Efficiency: 77% | LP Efficiency 80%