SPEC SHEET: Flare-VFF-70-H



VENT FREE FLARE-VFF-70-H

FLARE FRAMELESS MODERN VENT FREE FIREPLACE

SUBJECT	DETAILS						
Type of Glass	Natural Gas (NG) or Liquid Propane (LP)						
Safety Standard	CSA File # 263124 ANSI Z21.97 CSA 2.41						
Operation	Honeywell						
Electrical Requirements	110 Volts, 15 Amps (DEDICATED POWER RECOMMENDED)						
Glass Heights	16"		24"				
RGB LED System	Multi-Colored Interior RGB LED Lighting System						
Pilot Protection	4" Wind Guard						
Weight	IN CRATE		NO CRATE				
	359 lbs		251 lbs				
Firebox Protection	Stainless Steel Window Enclosures						
Burners	Multi-Row Stainless Steel Burner						
	CLEAR CRUSHED GLASS	ZIRCON BLACK DIAMOND		RAIN DROP DIAMOND			
Interior Media Options	REFLECTIVE BRONZE	NZE AQUA FIRE GLASS		CHESTNUT FIRE GLASS			
	BLACK FIRE GLASS	GOLD CRUSHED GLASS		BLACK CRUSHED GLASS			

Product Specifications

- The Flare Fireplace is certified for use with either Natural Gas (NG) or Propane (LP)
- The Vent Free Flare Fireplace system operates off open faced combustion.
- Clearances to combustible materials MUST be maintained. Refer to Installation Manual for clearance distances.
- The Vent Free Flare Fireplace must be properly installed in an outdoor environment with optimal air flow.
- The Vent Free Flare Fireplace must be installed according to requirements as presented in the <u>Installation Manual</u>, as well as complying with all local codes. If no codes exist, then the current CSA installation code must be followed.





Parts Included:

- Flare Fireplace
- Glass Wind Guard(s)
- Option of "Classic" Glass Media
- Complete Electronic ignition Pilot Assembly
- Spare Parts Kit
- AC Power Plug
- RGB-LED Light Kit

Optional Features & Accessories:

- Reflective Black Ceramic Back
- Stainless Steel Weather Covers
- Options of "Premium" Glass Media

Gas Pressure & Power Output

HONEYWELL												
MODEL	GAS	INLET PRESSURE		MANIFOLD PRESSURE	BTU INPUT	ORIFICE SIZE		BURNER SIZE (inches)				
	GAS	MIN.	MAX.	WANTOLD PRESSURE	BIOINPOI	Burner 1	Burner 2	Burner 1	Burner 2			
VFF-70-H	NG	7.0 " WC	8.0 " WC	5.4	71,000	1000	1000	30 1/2	30 1/2			
VFF-70-H	LP	10.0 " WC	11.0 " WC	10.4	85,400	480	480					

For more information on Flare or our amazing features please visit: https://www.flarefireplaces.com