

FLARE VENT-FREE LEFT CORNER 60" WITH 24" HIGH GLASS OUTDOOR FIREPLACE SKU: VFLC60H

<u>SUBJECT</u>	<u>DETAILS</u>					
GAS TYPE OPTIONS	Natural Gas (NG) or Liquid Propane (LP)					
FIREBOX CONSTRUCTION	Combination of 3.16 & 3.04 Stainless Steel					
SAFETY STANDARD	ANSI Z21.97/CSA 2.41 for Outdoor Gas Fireplaces					
GAS VALVE SYSTEM	Honeywell Electronic Ignition Valve System					
ELECTRICAL REQUIREMENTS	110 volts, 15 amps, GFI Protected, (Dedicated Breaker Recommended)					
FIREPLACE OPENING HEIGHTS	16" Regular Opening	24" High Opening				
LIGHTING SYSTEM	Multi-Colored RGB LED Light System					
BURNER(S)	Stainless Steel Burner(s)					
WEIGHT	IN CRATE (LBS)	UNCRATED (LBS)				
	220	150				
INTERIOR MEDIA OPTIONS	Flare Fireplaces Glass Media					

Vent Free Product Specifications

All Vent Free Flare Fireplaces are for outdoor operation only and can be run with Natural Gas (NG) or Liquid Propane (LP), using the Honeywell commercial gas valve. The gas type must be specified so the proper equipment can be provided for safe operation. All Vent Free Flare Fireplaces must be installed maintaining required clearance to combustibles and be installed according to Flare Fireplaces requirements as presented in the <u>Installation Manual</u>, while complying with all existing local codes. If no codes exist, then the current CSA installation standards must be followed.

MODELS	GAS	INLET PRESSURE	MANIFOLD PRESSURE	BTU	ORIFICE SIZE		BURNER SIZE	
VF-LC-60-H	(NG)	7-8" WC	5.4	67,700	800	800	26.7"	26.7"
VF-LC-60-H	(LP)	10-13" WC	10.4	62,100	320	320	26.7"	26.7"

PARTS INCLUDED WITH FIREPLACE PURCHASE

- 5" Wind Guard Tempered Glass Panel
- 1 Classic Media Selection
- Power Adapter
- RGB LED Lighting System

OPTIONAL ADD-ON ACCESSORIES AND FEATURES

- Reflective Back and Side Panel(s)
- Natural Gas or Liquid Propane Conversion Kit
- Extra Classic or Premium Media Options