

FLARE VENT-FREE RIGHT CORNER 80" WITH 16" GLASS OUTDOOR FIREPLACE
SKU: VFRC80

SUBJECT	DETAILS	
GAS TYPE OPTIONS	Natural Gas (NG) or Liquid Propane (LP)	
FIREBOX CONSTRUCTION	Combination of 3.16 & 3.04 Stainless Steel	
SAFETY STANDARD	ANSI Z21.97/CSA 2.41 for Outdoor Gas Fireplaces	
GAS VALVE SYSTEM	Honeywell Electronic Ignition Valve System	
ELECTRICAL REQUIREMENTS	110 volts, 15 amps, GFI Protected, (Dedicated Breaker Recommended)	
FIREPLACE OPENING HEIGHTS	16" Regular Opening	24" High Opening
LIGHTING SYSTEM	Multi-Colored RGB LED Light System	
BURNER(S)	Stainless Steel Burner(s)	
WEIGHT	IN CRATE (LBS)	UNCRATED (LBS)
	240	190
INTERIOR MEDIA OPTIONS	Flare Fireplaces Glass Media	

Vent Free Product Specifications

All Vent Free Flare Fireplaces are for outdoor operation only and can be run with Natural Gas (NG) or Liquid Propane (LP), using the Honeywell commercial gas valve. The gas type must be specified so the proper equipment can be provided for safe operation. All Vent Free Flare Fireplaces must be installed maintaining required clearance to combustibles and be installed according to Flare Fireplaces requirements as presented in the [Installation Manual](#), while complying with all existing local codes. If no codes exist, then the current CSA installation standards must be followed.

MODELS	GAS	INLET PRESSURE	MANIFOLD PRESSURE	BTU	ORIFICE SIZE		BURNER SIZE	
VF-RC-80	(NG)	7-8" WC	5.4	97,000	1300	1200	44.8"	26.7"
VF-RC-80	(LP)	10-13" WC	10.4	91,000	480	320	44.8"	26.7"

PARTS INCLUDED WITH FIREPLACE PURCHASE

- 5" Wind Guard Tempered Glass Panel
- 1 Classic Media Selection
- Power Adapter
- RGB LED Lighting System
- Storm Doors

OPTIONAL ADD-ON ACCESSORIES AND FEATURES

- Reflective Back and Side Panel(s)
- Natural Gas or Liquid Propane Conversion Kit
- Extra Classic or Premium Media Options