

FLARE VENT-FREE SEE THROUGH 70" WITH 24" HIGH GLASS OUTDOOR FIREPLACE  
SKU: VFST70H

| SUBJECT                   | DETAILS  |                  |
|---------------------------|--|------------------|
| GAS TYPE OPTIONS          | Natural Gas (NG) or Liquid Propane (LP)                            |                  |
| FIREBOX CONSTRUCTION      | Combination of 3.16 & 3.04 Stainless Steel                         |                  |
| SAFETY STANDARD           | ANSI Z21.97/CSA 2.41 for Outdoor Gas Fireplaces                    |                  |
| GAS VALVE SYSTEM          | Honeywell Electronic Ignition Valve System                         |                  |
| ELECTRICAL REQUIREMENTS   | 110 volts, 15 amps, GFI Protected, (Dedicated Breaker Recommended) |                  |
| FIREPLACE OPENING HEIGHTS | 16" Regular Opening  | 24" High Opening |
| LIGHTING SYSTEM           | Multi-Colored RGB LED Light System                                 |                  |
| BURNER(S)                 | Stainless Steel Burner(s)  |                  |
| WEIGHT                    | IN CRATE (LBS)   | UNCRATED (LBS)   |
|                           | 240  | 170              |
| INTERIOR MEDIA OPTIONS    | <a href="#">Flare Fireplaces Glass Media</a>                       |                  |

### Vent Free Product Specifications

All Vent Free Flare Fireplaces are for outdoor operation only and can be run with Natural Gas (NG) or Liquid Propane (LP), using the Honeywell commercial gas valve. The gas type must be specified so the proper equipment can be provided for safe operation. All Vent Free Flare Fireplaces must be installed maintaining required clearance to combustibles and be installed according to Flare Fireplaces requirements as presented in the [Installation Manual](#), while complying with all existing local codes. If no codes exist, then the current CSA installation standards must be followed.

| MODELS     | GAS  | INLET PRESSURE | MANIFOLD PRESSURE | BTU    | ORIFICE SIZE |      | BURNER SIZE |       |
|------------|------|----------------|-------------------|--------|--------------|------|-------------|-------|
| VF-ST-70-H | (NG) | 7-8" WC        | 5.4               | 75,000 | 1000         | 1000 | 30.7"       | 30.7" |
| VF-ST-70-H | (LP) | 10-13" WC      | 10.4              | 73,000 | 420          | 420  | 30.7"       | 30.7" |

### PARTS INCLUDED WITH FIREPLACE PURCHASE

- 5" Wind Guard Tempered Glass Panel
- 1 Classic Media Selection
- Power Adapter
- RGB LED Lighting System
- Storm Doors

### OPTIONAL ADD-ON ACCESSORIES AND FEATURES

- Reflective Back and Side Panel(s)
- Natural Gas or Liquid Propane Conversion Kit
- Extra Classic or Premium Media Options